

# ASB-6010A

The aluminium barrier with 6 m arm



- ▶ simple and fast mounting due to the "Plug & Go" principle: install, plug-in, ready!
- ▶ barrier arm can be easily shortened on site
- ▶ easily operated via integrated SOMMER radio receiver (FM 868.8 MHz\*)
- ▶ the automatic obstruction detection ensures optimum protection: when it contacts an obstacle the barrier opens automatically and ensures that no vehicle is clamped
- ▶ the operating force of our barriers is certified according to EN 12445 and EN 12453
- ▶ the barrier can be opened (disengaged) and engaged manually in any position (e. g. in case of power failure)
- ▶ pluggable and service-friendly motor control with a range of setting options
- ▶ numerous connection possibilities for accessory, e.g. light barriers (photo cell), induction loops, ...
- ▶ also available at SOMMER are support posts and torque support arms\*\*




integrated warning light with a clearly visible signal effect



robust, high-quality components for a longer service life



right-hand installation:  
item no. 7642V001



left-hand installation:  
item no. 7641V001

Simply great: You already have the choice between left and right hand installations while placing your order and do not have to adapt the barrier on site.

\* also available in FM 434.42 MHz  
\*\* recommended from a barrier arm length > 3 m.



## Technical data:

Barrier arm	max. 6 m
Weight	approx. 40 kg
Power supply	AC 230 V, 50/60 Hz
Motor power	80 W, DC 24 V
Standby	max. 2 W
Temperature range	-20°C / +60°C
Protection class	IP 44
Permitted cycles per day	max. 300

Last updated: 03/2013. Literal errors, errors and technical changes excepted.

Visit our homepage: [www.sommer.eu](http://www.sommer.eu)

SOMMER Antriebs- und Funktechnik GmbH  
Hans-Boeckler-Str. 21 - 27 • D-73230 Kirchheim/Teck  
phone: +49 (0) 70 21 / 80 01-0  
fax: +49 (0) 70 21 / 80 01-101  
e-mail: [info@sommer.eu](mailto:info@sommer.eu)

